




SPECIFICATIONS

| Size | Metric | British |
|----------------------------------|--------------|-----------------|
| Max. Working Height A | 10.00m | 32ft 10in |
| Max. Platform Height B | 8.00m | 26ft 3in |
| Overall Length © | 2.48m | 8ft 2in |
| Overall Width D | 1.15m | 3ft 9in |
| Overall Height(Rails Up) | 2.36m | 7ft 9in |
| Overall Height(Rails Down) | 1.83m | 6ft |
| Platform Size(Length×Width) | 2.27m×1.12m | 7ft 5in×3ft 8in |
| Platform Extension Size G | 0.90m | 2ft 11in |
| Ground Clearance(Stowed/Raised) | 0.10m/0.019m | 4in/1in |
| Wheelbase (| 1.87m | 6ft 2in |
| Turning Radius(Inside/Outside) | 0m/2.20m | 0in/7ft 3in |
| Tyres | φ381×127mm | φ381×127mm |

| Performance | | |
|---------------------------------|-------------|-------------|
| S.W.L | 450kg | 992lb |
| S.W.L On Extension | 113kg | 249lb |
| Max. Occupants (Indoor/Outdoor) | 2/2 | 2/2 |
| Gradeability | 25% | 25% |
| Travel Speed(Stowed) | 3.5km/h | 2.17mph |
| Travel Speed(Raised) | 0.8km/h | 0.50mph |
| Max. Working Slope | X-1.5°/Y-3° | X-1.5°/Y-3° |
| Up/Down Speed | 34/30sec | 34/30sec |
| - 1., 1 | | • |

| Weight | | | |
|----------------|--------|--------|--|
| Overall Weight | 2670kg | 5886lb | |

| Power | | |
|-------------------|-------------|-------------|
| Hydraulic Tank | 20L | 5.3gal |
| Lead-acid Battery | 24V/185Ah | 24V/185Ah |
| Lithium Battery | 24V/180Ah | 24V/180Ah |
| Charger | 24V/30A | 24V/30A |
| Lifting Motor | 15VAC/3.5kW | 15VAC/3.5kW |



CE EN 280







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- · Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











