


SPECIFICATIONS

Metric	British
15.70m	51ft 6in
13.70m	44ft 11in
2.84m	9ft 4in
1.39m	4ft 7in
2.62m	8ft 7in
2.09m	6ft 10in
2.64m×1.12m	8ft 8in×3ft 8in
0.90m	2ft 11in
0.10m/0.019m	4in/1in
2.22m	7ft 3in
0m/2.70m	0in/8ft 10in
φ381×127mm	φ381×127mm
	15.70m 13.70m 2.84m 1.39m 2.62m 2.09m 2.64m×1.12m 0.90m 0.10m/0.019m 2.22m 0m/2.70m

Performance		
S.W.L	250kg	551lb
S.W.L On Extension	113kg	249lb
Max. Occupants (Indoor/Outdoor)	2/0	2/0
Gradeability	25%	25%
Travel Speed(Stowed)	3.5km/h	2.17mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	72/67sec	72/67sec

Weight			
Overall Weight	3440kg	7583lb	

Power		
Hydraulic Tank	20L	5.3gal
Lead-acid Battery	24V/240Ah	24V/240Ah
Lithium Battery	24V/220Ah	24V/220Ah
Charger	24V/30A	24V/30A
Lifting Motor	15VAC/3.5kW	15VAC/3.5kW



CE EN 280





FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- · Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











