


SPECIFICATIONS

Size	Metric	British
Max. Working Height A	17.20m	56ft 5in
Max. Platform Height B	15.20m	49ft 10in
Overall Length ©	3.36m	11ft
Overall Width D	1.25m	4ft 1in
Overall Height(Rails Up)	3.24m	10ft 8in
Overall Height(Rails Down)	2.47m	8ft 1in
Platform Size(Length×Width)	3.04m×1.17m	10ft × 3ft 10in
Platform Extension Size G	1.20m	3ft 11in
Ground Clearance(Stowed/Raised)	0.15m/0.025m	6in/1in
Wheelbase (2.49m	8ft 2in
Turning Radius(Inside/Outside)	0.60m/3.00m	2ft/9ft 10in
Tyres	22×9×16	22×9×16

Performance		
S.W.L	500kg	1102lb
S.W.L On Extension	500kg	1102lb
Max. Occupants (Indoor/Outdoor)	2/0	2/0
Gradeability	30%	30%
Travel Speed(Stowed)	4.5km/h	2.80mph
Travel Speed(Raised)	0.4km/h	0.25mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	65/68sec	65/68sec

Weight			
Overall Weight	6280kg	13845lb	

45L	11.7gal
48V/320Ah	48V/320Ah
48V/60A	48V/60A
2×32VAC/3.3kW	2×32VAC/3.3kW
48VDC/10.0kW	48VDC/10.0kW
	48V/320Ah 48V/60A 2×32VAC/3.3kW





Self-propelled Scissor Lifts



FEATURES

Standard Items

- Proportional Joystick Controls
- · Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Solid Rubber Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Brake System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Tie-Down And Lifting Points
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











