


## **SPECIFICATIONS**

5.00m 5.00m	59' 1" 52' 6" 52' 6"
5.00m	52' 6"
88m	16'
	10
33m	7' 8"
23m	10' 7"
47m	8' 1"
88m×1.83m	16'×6'
43m/1.13m	4' 8"/3' 8"
30m	1'
86m	9' 5"
70m/5.50m	8' 10"/18'
15/55/D20	315/55/D20
2 2 3	33m 23m 47m 38m×1.83m 43m/1.13m 30m 86m 70m/5.50m

Performance		
S.W.L	680kg	1499lb
S.W.L on Extension	227kg	500lb
Max. Occupants(Indoor/Outdoor)	4/4	4/4
Gradeability	40%	40%
Travel Speed(Stowed)	≯6.0km/h	≯3.73mph
Travel Speed(Raised)(<11m/≥11m)	>1.0km/h >0.6km/h	>0.62mph >0.38mph
Max. Working Slope(<11m/≥11m)	2°/3° 1.5°/3°	2°/3° 1.5°/3°
Up/Down Speed	78/74sec	78/74sec

Weight			
Overall Weight	8980kg	19798lb	

Kubota Z482/9.8kW 110L	Kubota Z482/9.8kW 29gal
110L	29gal
	- 3 -
80L	21gal
48V/350Ah	48V/350Ah
48V/60A	48V/60A
32VAC/9kW	32VAC/9kW
32VAC/15kW	32VAC/15kW
	48V/60A 32VAC/9kW





**Scissor Lifts** 



## **FEATURES**

## Standard Items

- Drivable At Full Height
- Proportional Joystick Controls
- Self-lock Gate On Platform
- Dual Slide-Out Platform Extension Deck
- Four-Wheel Drive
- Two-Wheel Steering
- Drive axle
- Automatic Brake System
- Self-Weight Lowering System
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Alarm
- All Motion Alarm
- Horn
- Hour Meter
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- · Automatic Leveling Hydraulic Outriggers
- Anti-Restart Engine Protection
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Oscillating Axle Chassis



## ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











