


SPECIFICATIONS

Size	Metric	British
Max. Working Height (A)	32.00m	105ft
Max. Platform Height (B)	30.00m	98ft 5in
Overall Length ©	6.41m	21ft
Overall Width ①	1.40m	4ft 7in
Overall Height(Rails Up)	4.16m	13ft 8in
Overall Height(Rails Down)	3.17m	10ft 5in
Platform Size(Length×Width)	5.85m×1.20m	19ft 2in×3ft 11in
Platform Extension Size ©	1.90m	6ft 3in
Ground Clearance(Stowed/Raised)	0.19m/0.02m	8in/1in
Wheelbase (4.87m	16ft
Turning Radius(Inside/Outside)	2.60m/3.50m	8ft 6in/11ft 6in
Tyres	28×12-22	28×12-22

Performance		
S.W.L	750kg	1653lb
S.W.L On Extension	750kg	1653lb
Max. Occupants (Indoor/Outdoor)	2/2	2/2
Gradeability	30%	30%
Travel Speed(Stowed)	1.5km/h	0.93mph
Travel Speed(Raised)	0.1km/h	0.06mph
Max. Working Slope	1°(0°)	1°(0°)
Up/Down Speed	160/105sec	160/105sec

Weight			
Overall Weight	22200kg	48942lb	

220L	58gal
80V/520Ah	80V/520Ah
80V/80A	80V/80A
4×53VAC/2kW	4×53VAC/2kW
53VAC/28kW	53VAC/28kW
	80V/520Ah 80V/80A 4×53VAC/2kW



CE EN 280







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Four-Wheel Drive
- Four-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- · Drivable At Full Height



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











