DINGLI Exceed · New Height

SPECIFICATIONS


| Size | Metric | British |
|---------------------------------|-------------|--------------|
| Max. Working Height A | 35.00m | 114' 10" |
| Max. Platform Height B | 33.00m | 108' 3" |
| Overall Length C | 6.99m | 22' 11" |
| Overall Width D | 1.80m | 5' 11" |
| Overall Height(Rails Up) E | 4.15m | 13' 7" |
| Overall Height(Rails Down) F | 3.20m | 10' 6" |
| Platform Size(Length×Width) | 6.58m×1.60m | 21' 7"×5' 3" |
| Platform Extension Size G | 2.50m | 8' 2" |
| Ground Clearance(Stowed/Raised) | 0.20m/0.03m | 8"/1" |
| Wheelbase H | 5.32m | 17' 5" |
| Turning Radius(Inside/Outside) | 2.90m/3.80m | 9' 6"/12' 6" |
| Tyres | 28×16×22 | 28×16×22 |


| Performance | | |
|---------------------------------|------------|------------|
| S.W.L | 1000kg | 2204lb |
| S.W.L On Extension | 1000kg | 2204lb |
| Max. Occupants (Indoor/Outdoor) | 4/0 | 4/0 |
| Gradeability | 25% | 25% |
| Travel Speed(Stowed) | ≯1.6km/h | ≽0.99mph |
| Travel Speed(Raised) | ≽0.1km/h | >0.06mph |
| Max. Working Slope(X/Y) | 1°/0° | 1°/0° |
| Up/Down Speed | 180/240sec | 180/240sec |
| | | |


| Weight | | |
|----------------|----------|---------|
| Overall Weight | 27180kg | 59922lb |
| | 27 TOURG | 5992210 |

| Power | | |
|-----------------|-------------|-------------|
| Hydraulic Tank | 280L | 73gal |
| Lithium Battery | 80V/620Ah | 80V/620Ah |
| Charger | 80V/80A | 80V/80A |
| Driving Motor | 4×56VAC/6kW | 4×56VAC/6kW |
| Lifting Motor | 53VAC/28kW | 53VAC/28kW |









Exceed New Height



FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- Automatic One-Way Platform Extension Deck
- Four-Wheel Drive
- Four-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Drivable At Full Height



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219 Telephone: +86(572)8681688

E-Mail: export@cndingli.com

Https://en.cndingli.com

Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission. 2024-11

